

## Features

- ▶ Typical wavelength, 690nm
- ▶ Stabilized optical power 20mW
- ▶ Single supply voltage, 7~24V DC
- ▶ Line generator : Cylindrical glass lens
- ▶ Precisely adjustable line thickness
- ▶ Modulation : digital ~300KHz
- ▶ 3 elements optic structure  
(2 lens fixed, 1 lens mobile)
- ▶ Wire length : 30cm(standard) or custom
- ▶ Laser class : 3R,3B (IEC 60825-1)
- ◆ Option : Bracket & Power supply.

## Specification

### Optical

Optical power(mW)	20 (Tc=25°C)
LD power(mW)	35 (Max)
Wavelength(nm)	690 ±5
Focus Beam Wid(mm)	< 0.1 (at 300mm)
Collimated Beam Wid(mm)	<3 (at 10m)
Fan Angle ( ° )	15,30,45,60,90, 120
Line Pattern	Accurate Straight
Beam Quality	TEM00
Beam intensity Pattern	Gaussian
LD Pin Connection	Case Ground

### Electrical

Operating voltage(DC V)	7~24 ± 5%
Operating current(mA)	50 (Typ)
Drive circuit	APC
Operating Temp.(°C)	-10 ~ +60
Storage Temp.(°C)	-40 ~ +85

### Mechanical


Weight(g)	40 ± 0.5
Dimensions(mm)	16Φ X 120
Operating lifetime(h)	30,000~50,000 (@RT)
Housing material	Aluminum

## Description

The GS series laser diode module combines laser diode technology, 3 elements lens optics, and sophisticated electronics within a slim and light aluminum anodized housing. Specially, 3 lens structure compensates line beam's curve & unbalance and dot beam's accurate focused point.

This series of modules provides a high-brightness elliptical laser line, and have various wavelengths and optical output power. Applications include a measurement, positioning, lighting, alignment, guidelines, pointing, switching, leveling, and machine vision etc. Useful in a variety of medical, industrial, and scientific instrumentation, as well as general R&D work.

## Drawings



### \* Range of fan angle

Symbol	Angle	Line length [ mm ] (distance 1m)	
		Perpendicular	Inclined at45°
1D	15°	250	500
3D	30°	500	1200
4D	45°	830	2000
6D	60°	1160	3500
9D	90°	2000	About 5000
12D	120°	3400	About 8000

### Lanics Co., Ltd.

Room #703, 7F Woolim e-Biz Center  
170-5, Guro-dong, Guro-gu, Seoul, 152-050, Korea  
TEL : +82-2-2108-2255 FAX : +82-2-2108-2260

E-mail : [support@lanics.com](mailto:support@lanics.com)

[http:// www.lanics.com](http://www.lanics.com)